

Cyklony pionowe typ D / I – IV główne wymiary i ciężar urządzenia

Wielkość	Znamionowy przepływ gazu m ³ / h	Wymiary (mm)											
		A	C1	C2	D1	D2	D3	D4	d 1	d 2	HA	H8	H1
400	840-1540	145	275	200	400	355	250	160	14	-	1850	2030	520
450	1070-1950	165	310	225	450	400	280	160	14	-	2090	2280	585
500	1320-2400	180	342	250	500	450	315	160	14	-	2310	2620	650
560	1650-3000	205	385	283	560	500	355	200	14	-	2570	2800	730
630	2090-3800	230	433	318	630	560	400	200	18	-	2920	3180	820
710	2660-4850	260	493	358	710	630	450	200	18	-	3280	3570	925
800	3370-6150	290	548	398	800	700	500	200	18	-	3680	4000	1040
900	4290-7800	330	618	448	900	800	560	200	18	-	4150	4510	1170
1000	4880-8880	365	685	500	1000	900	630	200	18	-	4600	5000	1300
1120	6600-12000	405	767	561	1120	1000	710	250	22	18	5100	5630	1455
1250	8360-15200	455	856	631	1250	1120	800	250	22	18	5750	6230	1625
1400	10640-19400	510	958,5	706,5	1400	1250	900	250	22	18	6430	6970	1820
1600	13480-24600	580	1094	790	1600	1400	1000	315	22	18	7410	8020	2080
1800	17160-31200	655	1232,5	894,5	1800	1600	1120	315	22	18	8285	8970	2340
2000	19520-35520	730	1370	995	2000	1800	1250	315	22	18	9215	9975	2600