

## Cyklony pionowe typ Dc / IV główne wymiary i ciężar urządzenia

Wielkość	Znamionowy przepływ gazu m <sup>3</sup> / h	Wymiary (mm)										
		A	C1	C2	D1	D2	D3	D4	d 1	d 2	HA	H8
400	840-1540	145	276	200	400	355	250	160	18	-	1862	2037
450	1070-1950	165	311,5	225	450	400	280	160	18	-	2097	2293
500	1320-2400	180	344	250	500	450	315	160	18	-	2322	2534
560	1659-3000	205	386,5	283	560	500	355	200	18	-	2577	2612
630	2090-3800	230	435	318	630	560	400	200	18	-	2927	3190
710	2660-4850	260	490	358	710	630	450	200	22	-	3294	3685
800	3370-6150	290	550	398	800	700	500	200	22	-	3694	4015
900	4290-7800	330	621	449	900	800	560	200	22	-	4164	4626
1000	4880-8880	365	689,5	502,5	1000	900	630	200	22	-	4614	5012
1120	6600-12000	405	700	562,5	1120	1000	710	250	22	18	5140	5530
1250	8360-15200	455	858	633,5	1250	1120	800	250	22	18	5750	6230
1400	10640-19400	510	961	711	1400	1250	900	250	22	18	6430	6970
1600	13480-24600	580	1098	796	1600	1400	1000	315	22	18	7410	8020
1800	17160-31200	658	1235	894,5	1800	1600	1120	315	22	18	8285	8970
2000	19520-35520	730	1372	997	2000	1800	1250	315	22	18	9215	9975

Wielkość	Znamionowy przepływ gazu m <sup>3</sup> / h	Wymiary (mm)											Masa kG	
		H1	H2	H3	H4	H5	H6	H7	K	n1	s	w	Dc/I,II	III,IV
400	840-1540	520	963	1200	1710	1809	-	1932	460	1	-	-	85	90
450	1070-1950	585	1108	1350	1944	2034	-	2178	503	1	-	-	112	119
500	1320-2400	650	1273	1510	2139	2259	-	2412	562	1	-	-	136	144
560	1650-3000	730	1423	1665	2416	2514	-	2677	610	1	-	-	176	192
630	2090-3800	820	1603	1890	2741	2844	-	3042	670	1	-	-	257	277
710	2660-4850	925	1808	2135	3071	3285	-	3422	732	1	-	-	315	340
800	3370-6150	1040	1943	2400	3466	3809	-	3837	862	1	-	-	410	441
900	4290-7800	1170	2173	2700	3895	4059	-	4327	937	1	-	-	610	660
1000	4880-8880	1300	2413	3000	4317	4509	-	4795	1020	1	-	-	825	878
1120	6600-12000	1455	3035	3358	4767	5038	1883	5283	1120	2	1120	160	1100	1270
1250	8360-15200	1625	3485	3748	5453	5626	2103	5957	1250	2	1250	160	1600	1620
1400	10640-19400	1820	3880	4203	6045	6310	2413	6669	1400	2	1400	160	1855	2020
1600	13480-24600	2080	4456	4833	6969	7200	2729	7684	1600	2	1600	200	2500	2780
1800	17160-31200	2240	5061	5428	7796	8133	3114	8596	1800	2	1800	200	3765	4110
2000	19520-35520	2600	5630	6006	8687	9013	3432	9563	2000	2	2000	200	4545	5000